

## Technical Datasheet

<b>Article - No:</b>	TDS-RT250B-L	Revision: A0
<b>Remarks</b>	single use only	
<b>Specification</b>		
<b>Product name</b>	RT250B-L, 250µL Beckman robotic pipette tips, low retention	
<b>Production conditions</b>	Class 100,000 clean room production	
	No release agent is used	
	Motor molding	
<b>Classification</b>	CE/IVD	
<b>Dimensions</b>		
<b>Colour</b>	Clear	
<b>Nominal Capacity</b>	250µL	
<b>Sterile</b>	Yes	
<b>Material Characteristics</b>	polypropylene (PP), premium surface	
<b>Product Characteristics</b>	biologically inert	
	no heavy metals according to EC/94/62	
<b>Purity Grade</b>	free of RNase and DNase	
	free of pyrogen	
	free of PCR inhibitors	
	free of human DNA	
	free of endotoxins	
	free of ATP	
<b>Match the model</b>	FX/NX	
	Multimek AP96	
	Biomek3000	
<b>Shelf - Life</b>	36 months at controlled storage conditions	
<b>Packaging</b>	pcs per rack: 96	
	rack per case: 50	
<b>Storage</b>	Storage Temperature: 2°C-40°C, humidity 40%-80%	
	Keep clean, ventilated and out of direct sunlight	
<b>Approved by PakGent quality department</b>		