

Technical Datasheet

| | | |
|---|--|--------------|
| Article - No: | TDS-RT1000HX-L | Revision: A0 |
| Remarks | single use only | |
| Specification | | |
| Product name | RT1000HX-L, 1000 μ L Hamilton robotic conductive tips, low retention | |
| Production conditions | Class 100,000 clean room production | |
| | No release agent is used | |
| | Motor molding | |
| Classification | CE/IVD | |
| Dimensions | | |
| Colour | Black | |
| Nominal Capacity | 100-1000 μ L | |
| Material Characteristics | polypropylene (PP), premium surface | |
| Product Characteristics | biologically inert | |
| | no heavy metals according to EC/94/62 | |
| Purity Grade | free of RNase and DNase | |
| | free of pyrogen | |
| | free of PCR inhibitors | |
| | free of human DNA | |
| | free of endotoxins | |
| | free of ATP | |
| Match the model | Star [®] | |
| | Starlet | |
| | Nimbus [®] | |
| Shelf - Life | 36 months at controlled storage conditions | |
| Packaging | pcs per rack: 96 | |
| | rack per case: 60 | |
| Storage | Storage Temperature: 2°C-40°C, humidity 40%-80% | |
| | Keep clean, ventilated and out of direct sunlight | |
| Approved by PakGent quality department | | |