

Technical Datasheet

Article - No:	TDS-UFPT-F-200E-L	Revision: A0
Remarks	single use only	
Specification		
Product name	UFPT-F-200E-L, 200µL filter tips, low retention	
Production conditions	Class 100,000 clean room production	
	No release agent is used	
	Motor molding	
Classification	CE/IVD	
Dimensions	<p>The drawing shows a tapered filter tip. The total length is indicated as 60 with a tolerance of +0/-1. A specific section of the tip, including the filter and the base, is dimensioned as 11.8 ± 0.3.</p>	
Colour	Clear	
Graduation	moulded rings	
Nominal Capacity	1-300µL	
Material Characteristics	polypropylene(PP), premium surface	
	filter: high density polyethylene(PE)	
Product Characteristics	biologically inert	
	no heavy metals according to EC/94/62	
Purity Grade	free of RNase and DNase	
	free of pyrogen	
	free of PCR inhibitors	
	free of human DNA	
	free of endotoxins	
Shelf - Life	free of ATP	
	36 months at controlled storage conditions	
Packaging	pcs per rack: 96	
	rack per case: 50	
Storage	Storage Temperature: 2°C-40°C, humidity 40%-80%	
	Keep clean, ventilated and out of direct sunlight	
Approved by PakGent quality department		